
## shielde<u>x</u>



## Shieldex<sup>®</sup> Med-tex P70

115090213070

Raw Material 79 % Polyamide + 21 % Elastomer

Type of knit Stretch-Tricot

Metal Plated 99.9 % Pure Silver

Metal Content 20 ± 2 % Silver

Stretch Double stretch direction / elongation warp 160-210 % / weft 75-115 %

Total Weight  $100 \text{ g/m}^2 \pm 18 \%$ 

Total Thickness  $0.42 \text{ mm} \pm 15 \%$ 

**Roll Width** 135 ± 5 cm

Roll Lenght Max. 36 m

Temperature Range  $-30 \,^{\circ}\text{C}$  to  $80 \,^{\circ}\text{C}$ 

Storage and Handling According to our care and handling instructions

Compliance and Certification DIN EN ISO 9001:2015, REACH, RoHS

Alterations Reserved 01.05.2021/12 — The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at www.shieldex.de.