

# Technical Data Sheet



## Shieldex® Tuell

No.: 1101201111 (width 110 cm)

Purpose	Conductive knitted fabric for general use Antibacterial, Antiodor, Fungicidal Excellent thermal conductivity Shielding against EMI
Description	Knitted silver plated nylon fabric
Raw Material	100 % Nylon
Plating	99 % Pure Silver
Surface Resistivity	$\leq 1,4 \Omega/\square$
Temperature Range / Storage / Handling	-30 °C to 90 °C According to our care and handling instructions
Weight	35 g/m <sup>2</sup> /- 3 g + 5 g
Total Thickness	0.22 mm $\pm$ 10 %
Roll Width	110 cm /+ 3 - 2 cm
Roll Length	100 m -5/+15 m

## Compliance and Certification

DIN EN ISO 9001:2015  
REACH  
RoHS



# statex

Produktions- und Vertriebs GmbH

Kleiner Ort 11 - 28357 Bremen / Germany  
Tel: +49 421 27 50 47 - Fax: +49 421 27 36 43  
info@statex.de - www.statex.de

The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note as well our handling and storage instructions accessible at [www.statex.de](http://www.statex.de).

Alterations Reserved 28.12.2018/08